

---	--	---	--

SERVICE CONDITIONS			
SERVICE CONDITIONS	Required torque O (Nm) ...: 4000		Stem diam. (mm): 0,00
	Required torque C (Nm) ...: 4000	VALVE	Lead (mm): 0,00
	Number of turns in output ..: 0,25		Lift (mm): 0,00
	Closing direction: Clockwise		
	Customer specifications		
Observation			

ACTUATOR	
Actuator: SQ400	Actuator's speed (Rpm): 0,12

MECHANICAL SPECIFICATIONS	
Protection: _NotExplosionProof IP67	Output flange: F16
Box type: Standard	Output form: N/A
Class: III	Machining type: Foot plate / Lever
Output speed (RPM): 0,12	Manual command: Declutchable Ø 300 mm
Operating time (s): 125	Paint: BCPS-C3-01
Max torque (Nm): 4000 Permanent (Nm): 2000	Painting process: Intermediate Corrosi
Torque set O (Nm): 4000	Color: RAL 1015 LIGHT IVORY
Torque set C (Nm): 4000	
Temperature: Standard -20°C to 70°C	

MOTOR SPECIFICATIONS		
Motor: Electric 3Ph 400V 50Hz	Motor duty (%): S4 - 50	
Power (kW): 0,100	Nominal intensity (A) : 0,60	Starting current (A): 1,20

ELECTRICAL SPECIFICATIONS	
Control type: Switch	Wiring diagram: S5000038
Options (incl.): Transmitter 4/20mA TAM	
End of travel limit switches: Opening : 2 & Closing : 2 - Type : SPDT	
Torque limit switches qty: Opening : 1 & Closing : 1 - Type : SPDT	
Customer's connection: Plug plastic 3xM20 ISO	
Heater: 230 V 25 W	

PARTICULAR SPECIFICATIONS		
Quality level: Q3	Quality plan	Dimensional drawing ...: Z216404 Ver. A
Electronic card's configura: Standard		Orientations :